

Locker Unit Mifare

The Locker Unit Mifare is an electronic lock with an elegant design. Its reliability has been proven in many types of organizations, including financial institutions, hospitals, libraries, educational institution and offices. Users open their locker by simply holding their RFID access card close to the lock on the locker door. The red/green LED indication shows whether a locker is already in use.

- Can be used with every (existing) Mifare access card, wristband or keyfob
- Also reads HID, iClass and Legic card serial numbers (CSN)
- Equipped with a tamper alarm
- Easy to install
- Door position sensor
- Easy cabling; no batteries required



User friendliness

The Locker Unit Mifare is equipped with an integrated card-reader. This enables users to simply operate their locker by holding their RFID card close to the locker unit that is mounted into the locker door. This prevents users from queuing at a central terminal. Apart from lockers, this locker unit is also often used to secure access to filing cabinets and postboxes.

Reliability

The Locker Unit Mifare is designed for extreme reliability. For example; the lock has a pulling resistance of over 200kg. Furthermore, the integrated memory ensures that all locks 'remember' their status, even if there is a network failure or if a power blackout has occurred. The permanent connection with the Locker Terminal guarantees a reliable tamper alarm.

Ease of installation

The locks are equipped with a straightforward serial cabling. Because of this, they don't require batteries. The door position sensor ensures that the locks are easily adjustable.

Technical specifications

Dimensions	95 x 65 x 27 mm (LxWxH)
Weight	~0,13 kg
Housing	ABS
Protection	IP30
Pulling resistance	+200 kg
Temperature	Operating: 0 to 50 °C Storage: -20 to 70 °C
Humidity	10% - 90% (non condensing)
Certifications/approvals	CE: safety EN60950 EMC: immunity EN50082-2, emission EN50082-1
Power supply	24 VDC, 27 mA average, 100 mA peek (directly after power on or after locking/unlocking)
Connectors	2x RJ10 connectors for power supply and data, cabled in parallel
Card technology	CSN + sector data: Mifare ultralight, Mifare Classic, Mifare DESFire, Mifare plus (SL3) CSN only: HID, iClass, Legic Advant
Detection range	Handle: Card: 2cm, wristband: 2cm, keyfob: 2cm Flush: Card 3cm, wristband: 1,5cm, keyfob: 2cm
Frequency	13,56MHz

Article number

Locker Unit Mifare flush	9208020 - Locker Unit Mifare flush + Pin set long 9208030 - Locker Unit Mifare flush + Pin set short
Locker Unit Mifare handle light grey	9871500 - incl. lock and pinset
Locker Unit Mifare handle charcoal	9961968 - incl. lock and pinset

Subject to change without prior notification